

Technical Data Sheet

Plastlim/Muoviliima 25 ml 36-4014

Product description:

A quick drying adhesive suitable for bonding hard plastics such as PVC, ABS, Polycarbonate and Acrylic. Plastic Glue dries to a strong colourless bond and waterproof.

Applications:

Ideal for computers, mobile phones, fridge fitting, gutters and much more.

Product Specification:

Appearance	Viscous liquid
Odour	Aromatic odour
Specific gravity	0,87
Viscosity at 25 °C	2700-3200 centipoise
Solid	16 - 20 %
Application temperature	-10 to 40 °C
Service temperature	-10 to 60 °C
Shelf life	12 months

Directions:

1. Ensure surfaces are close fitting, clean, dry and free from grease or dust.
2. Use only on a suitable worktop and cover easily damaged surfaces.
3. Apply a thin film of glue over both surfaces, align parts and press firmly together holding in place until set. Full strength is achieved in 24 hrs at 21 °C (room temperature).
4. Remove excess adhesive with acetone taking care not to damage surrounding surface. This product works by dissolving the surface of the plastic, excess amount of adhesive may damage the surface.
5. Wipe excess adhesive from the tube and replace the cap. Return the tube to the blister pack and retain this for future reference.

Note: Plastic Glue is not recommended for use on polyethylene, polypropylene or uPVC. If in any doubt, test on small area before use. Always cover polished, painted or lacquered surfaces to avoid the possibility of damage.

Caution:

Avoid contact with eyes, skin and mouth. Use in well ventilated area. In case of contact with eyes, flush with water immediately for 15 minutes. If irritation persists, seek medical attention. Keep out of reach of children.

Storage:

Highly flammable, keep away from any heat source or naked flames. Store in dry and cool place with temperature below + 30 °C. Use within 12 months from date of production.