

TECHNICAL DATASHEET

MOTOR OIL 5W-40 FULLY SYNTHETIC

36-909, 36-915, 36-916

DESCRIPTION

Motor Oil 5W-40 Fully Synthetic is the ultimate synthetic engine oil designed for use in high performance passenger car engines where it offers full engine protection under the most severe conditions. The product is based on ultra stable synthetic base stocks combined with state of the art additive technology.

APPLICATION

Modern high performance petrol engines requiring the ultimate in performance and lubrication

CHARACTERISTICS

SAE Viscosity Grade		5W-40
Density @ 15°C		0.860
Kinematic Viscosity (mm ² /s)	@ 40°C	82.0
	@ 100°C	14.0
Viscosity Index (VI)		177
Pour Point (°C)		-39
Flash Point (°C)		220
Sulfated Ash (%)		1.1
Total Base Number (mgKOH/g)		10.1

PROPERTIES AND FEATURES

Catalyst compatible

Mixes with other oils

Helps to reduce emissions

BENEFITS

Ultimate oil for high performance engines

Low drag which means more power and lower fuel consumption

Reduced need for top-up through lower evaporation at high temperatures

Designed for use in modern passenger car petrol engines both turbo and non-turbo

2017-06-26

PERFORMANCE LEVEL

ACEA A3/B3, A3/B4

API SN

MB 229.3

VW 502.00/505.00

RN 0700/0710

MB 226.5

ENVIRONMENTAL PROTECTION/SAFETY PRECAUTIONS

Do not pour used oil down sewers or drains. Dispose of used oil at your nearest oil-recycling bank. Dispose of empty packs in a responsible manner. Store container in an upright position and secure when transported. Wear goggles if splashing risk. Avoid exposure to oil mist. When using oil do not eat, drink and smoke. Wash hands after use. Always refer to vehicle or engine manufacturers handbook to verify suitability of this product for the vehicle/engine.