

TECHNICAL DATASHEET

36-926, 36-9265 MOTOR OIL FULLY SYNTHETIC LONGLIFE 0W-30

DESCRIPTION

Motor oil fully synthetic Longlife 0W-30 is a technically advanced fully synthetic engine oil designed for the latest generation of petrol and diesel engines, to provide advanced levels of wear protection and performance compared to conventional oils, combined with enhanced fuel economy.

APPLICATION

Motor oil fully synthetic Longlife 0W-30 is recommended for modern vehicles including high-performance, turbo-charged, supercharged petrol and diesel multi-valve injected engines in passenger cars and light commercial vehicles where a 0W-30 oil is demanded by the vehicle manufacturers.

CHARACTERISTICS

SAE Viscosity Grade		0W-30
Density @ 15 °C		0.857
Kinematic Viscosity	@ 40 °C	57.0
(mm ² /s)	@ 100 °C	10.1
Viscosity Index (VI)		170
Pour Point (°C)		-44
Flash Point (°C)		214
Sulfated Ash (%)		1.4
Total Base Number (mgKOH/g)		9.0

PROPERTIES AND FEATURES

- Increased power due to low viscosity
- Lower oil consumption due to synthetic base stocks
- Reduced emissions due to improved fuel economy

BENEFITS

- Excellent engine performance under all driving conditions
- Enhanced frictional properties giving greater fuel economy
- Excellent cold weather starting and rapid circulation

PERFORMANCE LEVEL

- API SL/CF • ACEA A5/B5

ENVIRONMENTAL PROTECTION/SAFETY PRECAUTIONS

Do not pour used oil down sewers or drains. Dispose of used oil at your nearest oil-recycling bank. Dispose of empty packs in a responsible manner. Store container in an upright position and secure when transported. Wear goggles if splashing risk. Avoid exposure to oil mist. When using oil do not eat, drink and smoke. Wash hands after use. Always refer to vehicle or engine manufacturers handbook to verify suitability of this product for the vehicle/engine.