

# TECHNICAL DATASHEET

## SYNTHETIC MOTOR OIL

HELSYNTETISK MOTOROLJA  
 HELSYNTETISK MOTOROLJE  
 TÄYSSYNTETITTINEN MOOTTORIÖLJY  
 HELSYNTETISK MOTOROLJA

A3/B3, A3/B4 0W-40



### Meets the following specifications:

- ACEA A3/B3, A3/B4
- API SN/CF
- MB 226.5, 229.3, 229.5
- VW 502 00/505 00
- Porsche A40
- Ford WSS-M2C-937-A
- Renault RN 0700, RN 0710
- BMW LL-01

### Important information when changing engine oil:

Always check the amount of engine oil your engine should have. The information can be found in the vehicle's owner's manual. When changing the oil, the oil filter should also be changed.

#### TYPICAL CHARACTERISTICS

Synthetic motoroil 0W-40	Typ. value	Unit	Method
Density at 15 °C	843,1	kg/m <sup>3</sup>	ASTM D 4052
Kinematic viscosity at 100 °C	13,9	mm <sup>2</sup> /s	ASTM D 445
Kinematic viscosity at 40 °C	78,5	mm <sup>2</sup> /s	ASTM D 445
Viscosity index	183	mm <sup>2</sup> /s	ASTM D 2270
Total Base Number	10,3	mg KOH/ g oil	ASTM D 2896
Sulphated ash	1,07	%	ASTM D 874
Flash Point, COC	228	°C	ASTM D 92
Pour Point	<-52	°C	ASTM D 5950