

TECHNICAL DATASHEET

Motorcycle Oil Semi Synthetic 15W-40

36-957, 36-9570

DESCRIPTION

Motorcycle Oil Semi Synthetic 15W-40 is a high specification, semi-synthetic, motorcycle engine oil meeting API and JASO requirements. High quality base oils are blended with advanced additives to give high anti-wear and detergency properties, thus providing longer engine life and maintaining maximum performance in terms of power and efficiency. The oil meets the JASO T903:2006 MA requirements including the JASO MA2 category for improved clutch performance.

APPLICATION

Motorcycle Oil Semi Synthetic 15W-40 is suitable for 4-stroke air-cooled and liquid-cooled motorcycles requiring the specifications below

CHARACTERISTICS

SAE Viscosity Grade		15W-40
Density @ 15°C		0.885
Kinematic Viscosity (mm ² /s)	@ 40°C	99.2
	@ 100°C	13.9
Viscosity Index (VI)		142
Pour Point (°C)		-30
Flash Point (°C)		204

PROPERTIES AND FEATURES

- Good anti-wear protection
- Shear stable VI improver

2017-06-13

BENEFITS

- Outstanding engine cleanliness
- Improved clutch performance

PERFORMANCE LEVEL

API SL

JASO MA, MA2

ENVIRONMENTAL PROTECTION/SAFETY PRECAUTIONS

Do not pour used oil down sewers or drains. Dispose of used oil at your nearest oil-recycling bank. Dispose of empty packs in a responsible manner. Store container in an upright position and secure when transported. Wear goggles if splashing risk. Avoid exposure to oil mist. When using oil do not eat, drink and smoke. Wash hands after use. Always refer to vehicle or engine manufacturers handbook to verify suitability of this product for the vehicle/engine.